



Units : mm

## Half Height ATAPI CD-ROM Drive For Audio Device

### CD-5010B

- ATA/ATAPI ( IDE ) Interface
- Smooth and quiet operation than CD-ROM drives for PC\*
- Electrical emergency eject function on the bottom side.
- Low clamp noise.
- Firmware customizations available ( e.g. Tray road/eject speed. )
- CD-DA ( single session ) and data CD ( multi session ) supported

\*Compare with our products

Readable discs	CD	CD-ROM, CD-DA CD-R, CD-RW
Read Speed	CD-ROM	32x
	CD-R / RW	32x
	CD-DA	32x
	Play Audio	10x
Disc Diameter	12cm , 8cm	
Interface	ATA/ATAPI ( IDE )	
DATA Transfer Rate	Programmed I/O ( PIO )	16.6MB/s Max. ( Mode 0 to 4 )
	Multi-word DMA	16.6MB/s Max. ( Mode 0 to 2 )
	Ultra DMA	66.6MB/s Max.
Average Random Access Time	110ms ( CD-ROM 32x )	
Data Buffer	198KB	
Loading Mechanism	Tray Loading	
Environmental Condition	Ambient Temperature	Operating 5 to 45 °C
	Relative Humidity	Operating 20 to 80% ( non-condensing )
Power Requirements	DC5V ±5% / DC12V ±5%	
MTBF	60,000POH	
Dimensions	146.0W x 41.3H x 165.0D ( mm )	
Mass ( Weight )	700g or less	
Mounting Orientation	Horizontal	
Eject button	Not equipped	
Access indicator	Not equipped	
Drive configuration	Fixed as Slave or Master by firmware	
Analog Audio ( Line out )	Option	
RoHS Directive	Complied	



\* 記載の仕様は予告なく変更することがありますのでご了承ください。  
\* 記載されている会社名、製品名は各社の商標または登録商標です。

## ティアック株式会社

<http://www.teac.co.jp/>

周辺機器事業部 営業部

〒 206-8530 東京都多摩市落合1-47  
TEL 042-356-9152 FAX 042-356-9184

大阪営業所

〒 564-0052 大阪府吹田市広芝町4-1  
ミタカビル4F

TEL 06-6384-6041 FAX 06-6385-8849