



NEW Product Information

DVD Super Multi Drive DV-W28S-V

8x DVD±R **8x DVD+RW**
6x DVD±R DL **6x DVD-RW**

- Half inch height (12.7mm) standard design
- Buffer underrun Prevention
- Supporting disc-at-once, session-at-once, packet write, incremental, over write, track-at-once recording mode, sequential write, multi-session, and back ground format
- Horizontal and vertical mounting for most system configuration

Write Speed (Max Speed)	DVD+R	8x (CAV)	
	DVD+R DL	6x (ZCLV)	
	DVD-R	8x (CAV)	
	DVD-R DL	6x (ZCLV)	
	DVD+RW	8x (ZCLV)	
	DVD-RW	6x (ZCLV)	
	DVD-RAM	5x (ZCLV)	
	CD-R	24x (CAV)	
	CD-RW	US 24x (ZCLV)	
		HS	10x (CLV)
	MS	4x (CLV)	
Read Speed (Max Speed)	DVD-ROM	8x (CAV)	
	DVD±R	8x (CAV)	
	DVD+R DL (Finalized Disc)	8x (CAV)	
	DVD-R DL (Finalized Disc)	6x (CAV)	
	DVD±RW	8x (CAV)	
	DVD-RAM (4.7G)	5x (ZCLV)	
	CD-ROM	24x (CAV)	
	CD-R/RW	24x (CAV)	
	CD-DA (DAE)	24x (CAV)	
	Disc Diameter	12cm, 8cm	
Interface	SerialATA Revision2.6		
Data Transfer Rate	Gen1 i 1.5GB / sec		
Access Time	150ms (typ) DVD-ROM		
	140ms (typ) CD-ROM		
Data Buffer	2MB		
Loading Mechanism	Drawer Type		
Environmental Conditions	Ambient Temperatures	Operating	5 to 45°C
		Non Operating	-20 to 60°C
		Transportation	-40 to 65°C
	Ambient Humidity	Operating	8 to 80% (non-condensing) *
		Non Operating	5 to 95% (non-condensing) *
		Transportation	5 to 95% (non-condensing) *
Power Requirements	DC5V±5%		
Current Consumption	Standby / Sleep 45mA / 32mA (Average current max)		
	During starting / Seek 1500mA (Max, Spikes less 1ms)		
MTBF	60,000POH (10% duty)		
Safety / EMI Standards	UL, CUL, TÜV, CB, CE and BSMI		
Dimensions	128.0W x 12.7H x 129.4D (mm)		
Mass (Weight)	172g or less		
RoHS	Complied		

Remark
Please check the specification sheets for detailed conditions and other information.
* The maximum wet-bulb temp. is 29.4 degree C

DVD is a trademark of DVD Format/Logo Licensing Corporation registered in the U.S., Japan and other countries.

RW and COMPACT disc are trademarks of Koninklijke Philips Electronics N.V.

Corporate and product names are the respective trademarks or registered trademarks of the companies mentioned. Features and specifications are subject to change without notice. Precaution : To ensure safe handling and operation, read the Instruction Manual before use.

TEAC CORPORATION Data Storage Products Division

TEAC CORPORATION (<http://www.teac.co.jp>) 1-47 Ochiai, Tama-shi, Tokyo 206-8530 Japan Phone:81-42-356-9153 Fax:81-42-356-9184

TEAC AMERICA, INC. (<http://www.teac.com>) 7733 Telegraph Road, Montebello, California 90640, U.S.A. Phone:1-323-726-0303 Fax:1-323-727-7656

TEAC EUROPE GmbH. (<http://www.teac.de>) Bahnstrasse 12, 65205 Wiesbaden-Erbenheim, Germany Phone:49-611-71580 Fax:49-611-7158-392

TAIWAN TEAC CORPORATION (<http://www.teac.com.tw>) 3F No.45, Sec.1 Min Chuan E. Road, 104 Taipei, Taiwan R.O.C. Phone:886-2-2597-8608 Fax:886-2-2597-8591

TEAC ELECTRONICS (M) SDN BHD (<http://www.teac.com.my>) Lot 22, Batu Berendam Ftz III, Batu Berendam, 75350 Melaka, Malaysia. Phone:60-6-2843402 Fax:60-6-2843471

© Copyright TEAC CORPORATION 2009