



## DVD ROM Drive DV-28S-C

# 8X DVD Readable

# 24X CD Readable

- Half inch height ( 12.7mm ) standard design
- Zero Power ODD Support
- Horizontal and vertical mounting for most system configuration


Read Speed ( Max Speed )	DVD-ROM	8x ( CAV )
	DVD±R	8x ( CAV )
	DVD±R DL ( Finalized Disc )	8x ( CAV )
	DVD±RW	8x ( CAV )
	DVD-RAM ( 4.7G )	5x ( PCAV )
	CD-ROM	24x ( CAV )
	CD-R / RW	24x ( CAV )
	CD-DA ( DAE )	24x ( CAV )

Disc Diameter	12cm, 8cm
Interface	SerialATA Revision 3.1
Data Transfer Rate	Gen1 1.5Gbps
Access Time	150ms ( typ ) DVD-ROM 140ms ( typ ) CD-ROM
Data Buffer	512KB
Loading Mechanism	Drawer Type

Environmental Conditions		
Ambient Temperatures	Operating	5 to 50°C
	Non Operating	-20 to 60°C
	Transportation	-40 to 65°C
Ambient Humidity	Operating	8 to 80% ( non-condensing )*
	Non Operating	5 to 95% ( non-condensing )*
	Transportation	5 to 95% ( non-condensing )*

Power Requirements	DC5V±5%	
Loading / Ejecting Life	10,000 times or more	
Current Consumption	Standby / Sleep	63mA/63mA ( Average current max )
	During starting / Seek	1500mA ( Max. Spikes less 1ms )
MTBF	60,000POH ( 10% duty )	
Safety / EMI Standards	UL, cUL, TÜV, CB, CE, RCM, KC and BSMI	
Dimensions	128.0W x 12.7H x 129.4D ( mm )	
Mass ( Weight )	170g or less	
RoHS	Complied	

Remark	Please check the specification sheets for detailed conditions and other information.
	* The maximum wet-bulb temp. is 29.4 degree C



**DVD** is a trademark of DVD Format/Logo Licensing Corporation registered in the U.S., Japan and other countries.

**Compact Disc** is a trademark of Koninklijke Philips Electronics N.V.

Other company names, product names and logos in this document are the trademarks or registered trademarks of their respective owners. Features and specifications are subject to change without notice. Precaution: To ensure safe handling and operation, read the Instruction Manual before use.

## TEAC CORPORATION

TEAC CORPORATION (<http://www.teac.co.jp>) 1-47 Ochiai, Tama-shi, Tokyo 206-8530 Japan

TEAC AMERICA, INC. (<http://teac-ipd.com/data-storage/>) 1834 Gage Road Montebello, CA 90640, USA Phone : 1-323-726-0303 Fax : 1-323-727-7656

TEAC EUROPE GmbH. (<http://www.teac.de>) Bahnstrasse 12, 65205 Wiesbaden-Erbenheim, Germany Phone : 49-611-71580 Fax : 49-611-7158-392

TAIWAN TEAC CORPORATION (<http://www.teac.com.tw>) 3F No.45, Sec. 1 Min Chuan E. Road, 104 Taipei, Taiwan R.O.C Phone : 886-2-2597-8608 Fax : 886-2-2597-8591